

Extraction Nozzles

Effex

High vacuum



Nozzle type SHM for fume removal from Stick Electrodes, MIG/MAG and Cored Wire

Manufactured in painted aluminium. Supplied with magnetic clamp.

Type	Airflow (m ³ /h)	Width (mm)	Outlet (mm)	Weight (kg)	Art. no.
SMH 300	100 - 120	300	Ø 38	1.0	750429
SMH 400	100 - 120	400	Ø 38	1.2	750430
SMH 500	100 - 120	500	Ø 38	1.3	750431



Nozzle type SHMT for fume removal from Stick Electrodes, MIG/MAG and Cored Wire

Manufactured in painted steel. Supplied with 330 mm flexible steel hose, adapter SR 4550, and magnetic clamp.

Type	Airflow (m ³ /h)	Width (mm)	Outlet (mm)	Weight (kg)	Length (mm)	Art. no.
SHMT	120 - 175	Ø 90	Ø 45	1.15	410	750657



Nozzle type SHFA for fume removal from Stick Electrodes, MIG/MAG and Cored Wire

Manufactured in painted aluminium. Supplied with 500 mm flexible steel hose and magnetic clamp.

Type	Airflow (m ³ /h)	Width (mm)	Outlet (mm)	Weight (kg)	Art. no.
SHFA	120 - 145	150	Ø 38	1.1	750603



DESCRIPTION:

Design: Low noise dynamic design to maximise the capturing distance. Maximum durability and performance is guaranteed using Reglo high quality nozzles.

Know-how: All nozzles have been duly tested in order to present correct specifications for system design and the selection of extraction units. See recommended airflow.



Nozzle type UNM for fume removal from Stick Electrodes, MIG/MAG and Cored Wire

Manufactured in painted aluminium. Supplied with magnetic clamp.

Type	Airflow (m ³ /h)	Width (mm)	Outlet (mm)	Weight (kg)	Art. no.
UNM	140 - 175	200	Ø 38	1.0	750540

Extraction Nozzles

Effex



On-torch nozzles for MIG/MAG and Cored Wire welding guns

Supplied with 2.5 m hose Ø25 mm, adapter for hose Ø38 and Ø45. Nozzle of nickel plated brass.

Type	Airflow (m ³ /h)	Hose (mm)	Nozzle (mm)	Weight (kg)	Art. no.
OT - 25	110	Ø 25		0.5	750837



On request, all nozzles can be supplied with a vacuum clamp instead of a magnetic clamp.

GUIDE

RECOMMENDED

Type	Welding electrodes	MIG/MAG	GS FCAW	SS FCAW	Hose diam. mm	Airflow (m ³ /h) at 8 000-12 000 Pa
SHMT	x	x	x	x	45	150 - 175
SHM 300	x	x	x		38	100 - 120
SHM 400	x	x	x		38	100 - 120
SHM 500	x	x	x	x	45	110 - 120
SHFA	x	x	x		38	120 - 145
UNM	x	x		x	45	140 - 175
OT - 25		x	x		25	110

We reserve the right to make changes.



Reglo AS • Andebu Næringspark • NO-3158 ANDEBU • Norway
 Tel.: +47 33 43 02 80 • Fax: +47 33 43 02 81
 info@reglo.no • www.reglo.no