

WALL-MAN® 800



- No contact with the floor
- Made to order
- Non slip floor in cage
- Three dimensional movement
- ATEX approved



Construction	Welded Steel	
Finish	RAL 5015	
Payload	150 kg (1 person plus equipment)	
Controls	In cage: Up/Down; Left/Right; In/Out	At ground Level: Up/Down
Air Supply	6 - 8 bar. 350 litres per minute supplied via hoses on self-retracting hose reels. A compressed air outlet for air tools is provided in the cage.	

Key Dimensions	• Height of raised platform	3275 mm	(may be increased to a maximum of 4525 mm or reduced as required)
	• Height to top of upper rail	4170 mm	(may be increased to a maximum of 5420 mm or reduced in line with raised platform height)
	• Distance from wall to front of cage ...	1035 mm	(fully retracted)
		1835 mm	(fully extended)
	• Cage size (W x D)	900 x 720 mm.	

Installation The platforms are suspended from the upper rail which is fitted to the booth at high level. The bottom guide wheels run on a flat strip at the base of the booth walls and exert horizontal forces only. There is no direct contact with the floor.

Imposed Loads *The following data relates to the standard model only. For platforms with height or off-set variations; please ask for specific information.*

• Upper Rail, Vertical Load:	460 kg	• Lower Rail, Vertical Load:	0 kg
• Upper Rail, Horizontal Load:	97 kg	• Lower Rail, Horizontal Load:	97 kg

Drawings

